

DINGO



+ Additional protection + Handling

The design of its 3 handles provides extra protection to the switch and motor and facilitates its use in vertical works. nanuling
Its three handles enable it to be handled in a variety of positions and hose lengths, making vertical work easier.

ELECTRIC PORTABLE VIBRATOR





t Brushes feature an y automated disconnect e system and easy external I interchangeability.



TECHNICAL DATA

	MODEL	WEIGHT (Kg)	TENSION (V)	FREQUENCY (Hz)	POWER (W)	DIMENSIONS (LongxWidexHigh)
D	INGO 230V	5.8	2301~	50-60	2,300 W	345x244x229
D	INGO 115V	5.8	1151~	50-60	1,800 W	345x244x229

A built-in air filter keeps pollutants out of the engine.
Splash-protected resistant housing.
Includes a carrying strap.
Vibration frequency: 12,000 v.p.m.

FLEXIBLE TRANSMISSIONS

MODEL		LENGTH (m)	WEIGHT (Kg)	
TDX 0.6	TDXE 0.6	0.6	2.6	
TDX 1	TDXE 1	1	3	
TDX 1.5	TDXE 1.5	1.5	3.5	
TDX 2	TDXE 2	2	4	
TDX 2.5	TDXE 2.5	2.5	4.5	
TDX 3	TDXE 3	3	5	
TDX 4	TDXE 4	4	6	
TDX 5	TDXE 5	5	7	
TDX 6	TDXE 6	6	8	
CORRESPO	NDING POKER			

AX 40

AX 48 AX 58 AX 25

AX 32

t of the engine.

Transmission with increased protection at the poker's head connection end.

AX POKERS		ØØ2532	© 40	Image: O4858
MODEL	DIAMETER (mm)	LENGTH (mm)	WEIGHT (Kg)	PERFORMANCE (m³/h)
AX 25	25	285	0.8	10
AX 32	32	366	1.7	14
AX 40	40	335	2.2	17
AX 48	48	335	3.2	28
AX 58 58		344	4.5	35

4 double-sealed oil-lubricated bearings.

